Marshall

BROADCAST & PRO AV

CV355-27X-IP

HD60 27x with IP (HEVC) & 3GSDI



















The CV355-27X-IP 27X Optical Zoom IP (HEVC/SRT) Camera utilizes a professional grade 8.5-megapixel sensor to capture crisp HD video up to 1920x1080 at 60fps with support for all HD formats. Marshall's straight forward design and ease of use make this camera a valuable tool in a wide variety of broadcast and professional A/V applications. The CV355-27X-IP is suitable for use in networked HD and workflows where image quality and versatility are of utmost concern, including live broadcast productions, courtroom capture, corporate video, government assembly, sportscast, newscast, reality television, concerts, house of worship and many more.

PRODUCT FEATURES

- 8.5 Megapixel (1/2.5") HD sensor
- 27X Optical Zoom (5.5~150mm) 60° AOV
- **Supports:** 1092x1080p and 720p 60/59.94/50/30/29.97/25 fps, 1920x1080i 60/59.94/50 fps
- IP formats: SRT, DHCP, DNS, HTTP, HTTPS, IPv4, NTP, RTSP, RTCP, RTP, TCP, UDP
- IP (HEVC/SRT) and HDMI simultaneous outputs
- Ethernet I/O supports video, control, audio and PoE over a single cable
- RS232 and 3.5mm audio input with passthrough

SPECIFICATIONS

| Sensor | IMX317 |
|---|--|
| Optical Zoom | 27x |
| Digital Zoom | 12x |
| Angle of view (H) | 60° |
| Vertical Viewing Angle | e 35° |
| Diagonal Viewing Angle 68° | |
| Aperture | F1.66~F4.98 |
| Focal Length | f=5.56mm~150.29mm |
| Focus Distance | Wide: 1m ~ ∞ / Tele: 1.5m ~ ∞ |
| Field of View Wide I | Horizontal viewing angle=60° (+/-5%) |
| Tele Ho | rizontal viewing angle=3.2° (+/-5%) |
| Minimum Environmental illumination 10 lux | |
| Minimum illumination | 0.1 lux (F1.6, 50IRE, 30fps) |
| Stream | Dual Stream (Main/Sub) / Webpage |
| Streaming Protocol | RTSP / RTMP / RTMPS / SRT |
| Video Compression | HEVC (H.265) / AVC (H.264) / MJPEG |
| Audio Compression | G.711 / AAC |
| Preset | 256 |
| Focus System | Auto/ One-Push AF / Manual |
| Electronic shutter | 1/1 to 1/10000 sec |
| Exposure Control | Auto / Shutter Pri / Iris Pri / Manual |
| Gain Control | Auto, Manual |
| Brightness control | Yes |
| 3D NR | Yes |
| WDR | Yes |
| Backlight Compensation Yes | |
| White Balance | Auto, Manual R/B Gain |
| Flip / Mirror | Yes |
| Line In | x1 ; 3.5mm phone jack |
| Line Out | x1 ; 3.5mm phone jack |
| Audio Output | HDMI / 3G-SDI / RTSP / RTMP / SRT |
| Audio Type | Stereo, Unbalanced |
| Audio Compression Fo | ormat AAC |
| HDMI | xl |
| Audio Output | Yes |
| HDMI Color Format | RGB / YUV422 |
| 3G-SDI | x1 |
| Audio Output | Yes |
| Serial | RS232 |
| RS232 In | RS232 In ; Mini-Din xl |
| RS232 Out | RS232 Out ; Mini-Din xl |
| | |

©2025 Marshall Electronics, Inc. All rights reserved. Features, specifications, pricing, and dimensions are subject to change without notice. Visit our website for updates and information.