

Marshall

BROADCAST & PRO AV

CV605-BK CV605-WH

5x PTZ HD Camera (3GSDI & IP)



3GSDI

PoE

RS-232
CONTROL

TRS AUDIO

IP H.264
STREAMING

IP H.265
HEVC

5X OPTICAL
ZOOM

Onvif

The CV605 5X optical zoom 3GSDI camera utilizes a professional grade 2 Megapixel sensor to capture crisp HD video starting at a wide-angle 85° and up to 1920x1080p resolution at 60fps. Multiple available outputs include 3GSDI and IP (H.265/H.264). Marshall's straight forward design and ease-of-use make this camera an affordable camera for a wide variety of broadcast and professional A/V applications. CV605-BK/WH can be setup through the one-cable to camera setup which uses one Ethernet (CAT) cable to carry power, video, audio, and control over IP.

PRODUCT FEATURES

- 2 Megapixel (HD) sensor
- 5X Optical Zoom (3~15mm) - starting at 85° AOV
- HD Resolution: 1920x1080p, 1920x1080i & 1280x720p
- Resolution/Framerate choices:
 - 1920x1080p at 60/59.94/50/30/29.97/25fps
 - 1920x1080i at 60/59.94/50fps
 - 1280x720p at 60/59.94/50/30/29.97/25fps
- Low Illumination capability at 0.5Lux (F1.8) for challenging environments
- 3G-SDI (BNC) and IP (H.265/H.264) with RS232 via RJ45
- Ethernet IP supports video, audio, control, and PoE (IEEE802.3af) over one Cat cable
- Control Options: IR remote, GUI, VS-PTC-200 (RS232/RS422), VS-PTC-IP (IP/RS232/RS422) or Custom
- 3.5mm audio (Line or Mic level) input (AAC, MP3, G.711A compression)



Mount Accessories

- CV605-WM
Wall Mount for CV605-series cameras (back)
- CV605-WMW
Wall Mount for CV605-series cameras (white)
- CV605-CM
Ceiling Mount for CV605-series cameras

©2021 Marshall Electronics, Inc. All rights reserved. Features, specifications, pricing, and dimensions are subject to change without notice. Please visit our website for updates and information.

Toll Free: (800) 800-6608 | www.marshall-usa.com | support@marshall-usa.com