

# Marshall

BROADCAST & PRO AV

## CV625-TBN/TWN

25X UHD60 NDI HX2/ NDI HX3 PTZ  
Auto Tracking with Dual Cameras



25X OPTICAL ZOOM

3GSDI

SRT READY

HDMI

RS-232 CONTROL

IP H.264

ULTRA HD

USB 3.0

FreeD

AUTO TRACK



## PRODUCT OVERVIEW

Marshall CV625-TBN/TWN PTZ cameras feature AI tracking, following, and framing to deliver a more accurate, smoother, self-adjusting presentation. The 4k UHD CV625 cameras feature a high-performance 8-Megapixel 1/1.8-inch sensor to capture crisp, high-quality UHD video. The camera delivers up to 3840 x 2160 resolution at 60 frames per second (fps) with an 60-degree horizontal angle of view. The second static camera is a wide-angle view camera made for that panoramic angle of view. Streamline your workflow with Marshall's AI Auto-Tracking PTZ cameras and NDI® HX2/ NDI HX3 network solution.

The CV625 offers versatility for various applications with its range of outputs, including 4K HDMI/RTSP/NDI streaming, Full HD 3G-SDI, Ethernet, and USB 3.0. Combining a 2-camera featured set for both remote and live installations, where the versatility of having a panoramic view of the area and a focused view of the subject or content is vital.

## PRODUCT FEATURES

- Accurate auto-track, follow and frame
- 8 Megapixel FHD Sensor (1/1.8") – 2160p, 1080p, & 720p (progressive), and 1080i (interlaced HDMI Output only)
- 3G-SDI, HDMI, Ethernet and USB outputs
- 25x optical zoom (7.1 mm ~ 171.95mm) starting at 60° H.AOV, and fixed base M12 lens camera at 83° H.AOV
- 340° pan and 120° tilt range with selectable PTZ maneuver speeds
- IP formats: VISCA / VISC over IP / ONVIF / NDI
- Stream Protocols: RTSP / RTMP / RTMPS / SRT / NDI HX2/ NDI HX3
- 3.5mm TRS Stereo Audio Input (Line In) embedding on all available outputs
- PoE+ (IEEE802.3at), DC: 23.5W (max), PoE: 24.5W (max)

Toll Free: (800) 800-6608 | [www.marshall-usa.com](http://www.marshall-usa.com) | [support@marshall-usa.com](mailto:support@marshall-usa.com)

